



Description:

It has a wide range of applications. It works with the professional amplifiers and audio processors. It is suitable for outdoor mobile performances, large multi-function halls, conference halls, etc.

Feature:

- * Birch housing, small size, light weight, and wear-resistant spray painting treatment.
- * It consists of two 15" subwoofer units, two 10" mid-woofer units, and four 1.7" tweeter drivers, providing sounds with high sensitivity and strong penetration.
- * The frequency divider in precise design can optimize power response and the vocal MF performance.
- * The linear array design allows 0-14 degrees of adjustment coverage area of the speakers, and has the advantages of compact and light combination, and convenient engineering assembly.

Specification:

Model	TX-1510
Rated power	Woofer 800W + full-range speaker 600W
Peak power	5600W
Nominal impedance	Woofer 4Ω/full-range speaker 16Ω+16Ω
Frequency range	45Hz-20KHz
Sensitivity	101dB
Max SPL(rated/peak)	132dB/138dB
Subwoofer	15" subwoofer ×2
Mid-tweeter	10" mid-woofer ×2 + 1.7" compressed drive ×4
Horizontal coverage angle(-6dB)	110°
Vertical coverage angle(-6dB)	10°
Weight	53.5kg
Size (H×W×D)	Full-range speaker: (275+220)×500×355mm Woofer: 440×700×800mm