



Feature

- * This Unit microphone adopts 48KHZ sampling rate, which is higher than the CD sound quality, more clear and bright. Built in DSP audio processor and no “poop-poop” low frequency sound.
- * Built-in HIFI speaker. With the function of volume adjustment and suppressing howling. When the microphone is turned on, the built-in speaker will automatically turn off.
- * With a 3.5mm outlet socket, it can be used for recording and connecting earphones.
- * In the voice control mode, both the chairman unit and the delegate unit can turn on the microphone by voice control and the sensitivity of the voice control can be adjusted. After the delegate microphone is turned on, it will automatically turn off the microphone if it does not speak for 30 seconds (default, the time can be set). The chairman unit is not restricted by this .
- * With 5-segment EQ adjustment function, different sound effects can be adjusted according to the voice characteristics of the speaker, which can achieve perfect results.
- * The chairman unit has priority function, which can turn off all delegate microphones that are speaking.
- * It adopts 100M network transmission to realize hand-in-hand cascade, and long-distance transmission will not have any impact on sound quality.
- * The use of capacitive touch buttons can effectively prevent button knocking and ensure a good venue environment.

Specification

Model	TS-0202D
Microphone Type	Cardioid directional electret
Frequency Response	80Hz-16KHz
Impedance	≥1KΩ
Sensitivity	-34±2dB (0dB=1V/Pa at 1kHz)
MAX SPL	125dB (THD>3%)
SNR	>80dB(A)
THD	<0.1%
Power Consumption	3W
Headphone load	16-32Ω
MAX Headphone Volume	40mW
Headphone Jack	3.5mm interface
Standard	IEC60914
Connector	Comes with 1.8m aviation 6 core
Power Supply	Host power supply
Color	Black
Sign-in function	Touch the button to sign in
Installation method	Desktop
Weight	0.86Kg
Microphone height	220mm
Dimension (L×W×H)	144×128×62mm